

**ORANGE  
EXTENDED LIFE TECHNOLOGY**



**ANTIFREEZE + COOLANT**

**COOL**

**ENGINEERED FOR VEHICLES REQUIRING ORANGE EXTENDED LIFE COOLANT  
5 YEARS / 150,000 MILES\***

## DESCRIPTION

PEAK® COOL Antifreeze + Coolant is specially engineered for use in automotive and light duty vehicles requiring orange extended life coolant. It's an advanced formula that features long lasting inhibitors providing long term protection against damaging rust and corrosion.

## FEATURES & BENEFITS

- Up to 150,000 miles or 5 years of maximum protection\*
- Meets European phosphate-free and Japanese silicate-free requirements
- Meets the performance requirements of ASTM D3306 and D4985

## APPLICATIONS

PEAK® COOL Antifreeze + Coolant is designed for use in GM vehicles 1995 and up, Chrysler vehicles 2013 and up, and Ford vehicles 2011 and up.

Best performance is achieved when a complete flush & fill is performed using PEAK® COOL Antifreeze + Coolant.

\*See warranty details at [PEAKGuarantee.com](http://PEAKGuarantee.com)



## FREEZE/BOIL PROTECTION CHART

PROTECTION		^Using a 15 psi (103 Pa) pressure cap	
Coolant/Water Ratio	PROTECTS FROM		
	Freezing Down to	Boiling Up to <sup>Δ</sup>	
40/60	-13°F (-25°C)	260°F (127°C)	
50/50	-34°F (-37°C)	265°F (129°C)	
60/40	-62°F (-52°C)	270°F (132°C)	



**Available in both 50/50 Prediluted  
and Concentrate**

**ORANGE  
EXTENDED LIFE TECHNOLOGY**



**ANTIFREEZE + COOLANT**

PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Orange	Orange	Distinctive
pH, 50 vol %	D1287	8.3	8.3	7.5-11.0
Specific gravity	D1122	1.125	1.066	1.110-1.1451/ 1.065 min <sup>2</sup>
Boiling point <sup>3</sup> , °F (°C)	D1120	325 (162.8)	229 (109)	226 (108) min.
Freezing point, °F (°C)	D1177	-	-36.2 (-37.9)	-34 (-36.4) max
Effect on Automotive Finish	D1882	No Effect	No Effect	No Effect
Total water, mass %	D1123	<5	50	5 max <sup>1</sup>
Ash content, mass %	D1119	<5	<2.5	5 max <sup>1</sup> /2.5 max <sup>2</sup>
Chloride, ppm	D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

<sup>1</sup>For concentrate product only, <sup>2</sup>Prediluted (50/50) only, <sup>3</sup>Unpressurized

## SHIPPING INFORMATION



### CONCENTRATE

PRA0L3

**1 Gallon Bottle**  
0-74804-03328-1

**6/1 Gallon Case**  
1-00-74804-03328-8

**PRA0L1**  
**55 Gallon Drum**  
0-74804-03365-6

**PRA0L8**  
**275 Gallon Tote**  
0-74804-05288-6



### 50/50 PREDILUTED

PRAL53

**1 Gallon Bottle**  
0-74804-03329-8

**6/1 Gallon Case**  
1-00-74804-03329-5

**PRAL51**  
**55 Gallon Drum**  
0-74804-03366-3

**PRAL58**  
**275 Gallon Tote**  
0-74804-07425-3

Part #	Unit	Pack/Size	Dimensions	Unit Wt. (lbs.)	Units per Pallet	Pallets per Truck	Pallet Weight**
PRA0L3	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,217
PRAL53	Case	6/1 Gal	15.8" L x 12.6" W x 12.25" H	58	36	20	2,145
PRA0L1	Drum	55 Gal	23.5" dia. x 34.5" H	525	4	20	2,157
PRAL51	Drum	55 Gal	23.5" dia. x 34.5" H	553	4	20	2,269
PRA0L8	Tote	275 Gal	40" L x 40" W x 46" H	2,679	1	14	2,679
PRAL58	Tote	275 Gal	40" L x 40" W x 46" H	2,503	1	14	2,503

\*\*Includes pallet weight of 50 lbs each

## ADDITIONAL INFORMATION

**Testing Requirements:** For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

**Storage Recommendations:** PEAK® COOL Antifreeze + Coolant can be stored in original container at ambient temperature with limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

**Safety and Environmental Guidance:** PEAK® COOL Antifreeze + Coolant contains virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from [peakauto.com](http://peakauto.com). Always dispose of used coolant in accordance with local, state and Federal guidelines.

**Old World Industries**  
Northbrook, IL 60062 • 800-323-5440  
[Peakauto.com](http://Peakauto.com)

To order, please call  
**Old World Industries Customer Service at**  
**1-800-323-8755**

Manufactured for Old World Industries, Northbrook, IL 60062 • (800) 289-7234  
MADE IN THE USA OF DOMESTIC AND FOREIGN CONTENT  
©2022 Old World Industries, All Rights Reserved.  
PEAK, PEAK & Mountain Graphic are trademarks of Old World Industries.

